

Safe-R

Superior Performance
Phenolic Insulation

SR/FB

Insulation for
Solid and Suspended Ground Floors

The wall insulation shall be Xtratherm Safe-R SR/FB manufactured to EN 13166 by Xtratherm, comprising a rigid Phenolic core between low emissivity foil facings. The SR/FB __mm with Agrément declared Lambda value as low as 0.020W/mK to achieve a U value of __W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 12, F30 155, K10 15, K10 205, K10 25, P10 180

Insulation

Phenolic Rigid Foam

Standard

BS EN 13166

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Face size

2400 x 1200 mm

Edge profile

Straight Edge

Thickness

50mm / 60mm / 75mm / 80mm /
100mm / 120mm

Product reference

Xtratherm Safe-R SR/FB
Steel & Timber Frame Insulation

Other sizes available dependent on quantity & lead time.