

Thin-R

PIR Insulation

FR/MG

Insulation for
Single Ply Fully Adhered Systems

The flat roof insulation shall be Xtratherm Thin-R FR-MG ___mm thick manufactured to EN 13165 by Xtratherm Comprising a rigid Polyisocyanurate (PIR) core between mineral glass facings with a Agrément declared Lambda value as low as 0.024 W/mK. The flat roof insulation shall be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause J42 420, J42 10

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 11/4878. Issue date: 15 August 2015
BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

1200 x 600mm

Edge Profile

Straight Edge

Thickness

25mm / 40mm / 50mm / 60mm / 70mm /
80mm / 90mm / 100mm / 110mm / 120mm

Product reference

Xtratherm Thin-R FR-MG Flat Roof
Insulation

Other sizes available dependent on quantity & lead time.