

Thin-R

PIR Insulation

Walk-R

Insulation for
Loft Decking at Ceiling Level

The roof insulation shall be Xtratherm Thin-R Walk-R manufactured to EN 13165 by Xtratherm, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings bonded to OSB Board. The Walk-R 86mm with __ __mm Mineral Wool to achieve a U value of __ __W/m²K for the roof element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause P10 10, P10 135

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

1200 x 600 mm

Thickness

86mm

Edge Profile

Available as Straight Edge or T&G
(Insulation only)

Product reference

Xtratherm Thin-R Walk-R Ceiling
Insulation

Other sizes available dependent on quantity & lead time.