

# XtroLiner

Superior Performance PIR Insulation

# XO/STP

Insulation for  
Soffit Application

The soffit insulation shall be Xtratherm XtroLiner XO/STP \_\_ \_mm manufactured to EN 13165 by Xtratherm, comprising a rigid modified Polyisocyanurate (PIR) core with a Agrément declared Lambda value of 0.021 W/mK and textured robust low emissivity foil facings with 6mm building panel. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause P10 185, P10 217

## Insulation

Modified Polyisocyanurate Rigid Foam

## Standard

BS EN 13165

## Certification

BS EN ISO 9001 Quality Management System  
BS EN ISO 14001 Environmental Management System

## Manufacturer

### Xtratherm UK Limited

Holmewood Industrial Park, Holmewood  
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

[info@xtratherm.com](mailto:info@xtratherm.com)[www.xtratherm.com](http://www.xtratherm.com)

### Xtratherm Limited

Liscarton Industrial Estate, Kells Road,  
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

[info@xtratherm.ie](mailto:info@xtratherm.ie)[www.xtratherm.ie](http://www.xtratherm.ie)

## Face size

2400 x 1200 mm

## Edge profile

Straight Edge

## Thickness

56mm / 66mm / 81 mm / 86mm /  
106mm / 126mm

## Product reference

Xtratherm XtroLiner XO/STP  
Soffit Insulation

Other sizes available dependent on quantity & lead time.