

XtroLiner

Superior Performance PIR Insulation

XtroWall Plus

Insulation for
Partial Fill Cavity-Wall

The partial fill cavity wall insulation shall be Xtratherm XtroLiner XO/XWP manufactured to EN 13165 by Xtratherm, comprising a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings and engineered shiplap jointing. The XtroWall Plus ___mm with a declared Lambda value of 0.020 W/mK to achieve a U value of ___W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 155, F30 12

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm Limited

Liscarton Industrial Estate, Kells
Road, Navan, Co.Meath, Ireland,
C15 NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

1200 x 450 mm

Edge profile

Shiplap Jointing

Thickness

110mm

Product reference

Xtratherm XtroLiner XtroWall
Partial Fill Cavity Wall
Insulation