

# CavityTherm<sup>®</sup>

Built-in Full Fill Wall Insulation

# CT/PIR

Insulation for  
Full Fill Cavity Walls

The built in full fill cavity wall insulation shall be Xtratherm CavityTherm CT/PIR manufactured to EN 13165 by Xtratherm, including corner boards and ancillary detail components, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings with engineered HIPS outer skin. The CT/PIR\_ \_ \_mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U value of \_ \_ \_W/m2K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 150, F30 12

## Insulation

Polyisocyanurate Rigid Foam

## Standard

BS EN 13165

## Certification

BBA Certification No. 10/4786. Issue date: 21 March 2019  
BS EN ISO 9001 Quality Management System  
BS EN ISO 14001 Environmental Management System

## Manufacturer

### Xtratherm UK Limited

Holmewood Industrial Park, Holmewood  
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.com](http://www.xtratherm.com)

### Xtratherm Limited

Liscarton Industrial Estate, Kells Road,  
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.ie](http://www.xtratherm.ie)

## Face size

1200 x 450 mm

## Edge profile

Rebated all four edges

## Thickness

75 mm / 90 mm / 100 mm / 110mm /  
125 mm / 150mm

## Product reference

Xtratherm CT/PIR Full Fill Cavity  
Wall Insulation

Other sizes available dependent on quantity & lead time.